



Ø 122 mm

Ø 178 mm

Ø 238 mm

81-3506
81-3509

81-3507
81-3510

81-3508
81-3511

! Bei einer Umrüstung der Leuchte auf die LED-Module gehen die Produkthaftung sowie
 • die Gewährleistung auf das umrüstende Unternehmen bzw. die umrüstende Person über.



81-3506
81-3509

81-3507
81-3510

81-3508
81-3511



Art.Nr.	W	V	K	mittl. LD	Lm	Winkel	EEK	Ø mm	H mm
81-3506	12 W	230 V	3.000 K	30.000 h	1.200 lm	120°	F	122	38
81-3507	20 W	230 V	3.000 K	30.000 h	2.350 lm	120°	E	178	38
81-3508	30 W	230 V	3.000 K	30.000 h	3.250 lm	120°	F	238	38
81-3509	12 W	230 V	4.000 K	30.000 h	1.450 lm	120°	E	122	38
81-3510	20 W	230 V	4.000 K	30.000 h	2.400 lm	120°	E	178	38
81-3511	30 W	230 V	4.000 K	30.000 h	3.300 lm	120°	E	238	38

- LED Austauschmodul für Wand- und Deckenleuchten mit Glüh- oder Energiesparlampen
- Befestigung durch Magnete
- Direktanschluß an 230 V
- breiter Abstrahlwinkel für schattenfreie Ausleuchtung
- Leuchte mit integriertem LED Treiber



81-3506



81-3507



81-3508



81-3509



81-3510



81-3511